



MATTICKS INDUSTRIES, INC.



KOOLGUARD

WALL MOUNT AIR CONDITIONING

(COOLING w/ELECTRIC HEAT)

**GENERAL PURPOSE INTERIOR **

CLASS 1, GROUP BCD, DIVISION 2 EXTERIOR



...230 Volt 1Ph , 230 Volt 3Ph, 460 Volt 3Ph @ 60Hz

Features:

...Heavy duty ultra-quiet operation for versatile applications such as new construction, modular analyzer shelters, control rooms, electronic equipment shelters, battery rooms, chemical storage containers, and many other hazardous locations that require environmental control.

...Aluminum finned copper coils: Grooved tubing and enhanced louvered fin for maximum heat transfer and energy efficiency.

...Twin indoor blowers: Move air quietly. Single speed blower motor provides maximum room circulation and low static operation.

...Compressors: Reciprocating compression designed to withstand higher compressor ratios. Scroll compressors for increased efficiency, quieter operation and reliability on 4 and 5 ton models.

...Electrical components: Electrical components are enclosed in approved explosion proof enclosures within the unit and are easily accessible for routine inspection and maintenance.

Dust Filters: One inch disposable air filters are standard with the return air filter grill and are replaceable from the room side.

...Electrical heat strips: Low watt density, stainless steel finned strip elements furnished on Electric Heat Models, with automatic high limit thermal cut-off safety control. Heaters are also shut off on blower failure. Both these shut down features require manual reset before restarting.

...Fresh Air make up: Barometric fresh air dampers are standard on all units, allowing up to 25% outside fresh air where needed. Where closed loop circulation is required this damper is permanently closed. Fresh air from a safe location above the roof line is furnished using a volume controlled filter plenum and stack. Also offered is our stack support designed for stacks up to 25' above grade without the use of guy wires.

...Full length mounting brackets: For improved appearance and easy installation. Note: Bottom mounting bracket included to assist in installation.

...Cabinet finish with baked on beige enamel, which allows it to withstand 1000 hours of salt spray

...Unit panel controls can be removed from the return grill and located away from the air flow

...Rain Flashing supplied with each unit

Options:

...Polyurethane enamel corrosion protected hermetic system, includes evaporator coil, condenser coil, compressor, and all connecting tube

...Polyurethane enamel coating of entire unit. Custom colors available

...Fresh Air Plenum and Stack with Rain Cap

...Loss of flow Alarm Contacts

...Low Ambient Control

...Stainless Steel Housing

Electric Heat Models :

18,000/11700 BTU to 58,000/18800 BTU @ 230/208 Volt 1Ph 60Hz

24,000/14000 BTU to 70,000/18800 BTU @ 230/208 Volt 3Ph 60Hz

31,000/15600 BTU to 68,000/18800 BTU @ 460 Volt 3Ph 60Hz

DEMINSIONAL SPECIFICATIONS

MODEL	LENGTH	HEIGHT	DEPTH	SUPPLY AIR OPENING	RETURN AIR OPENING
18,000 - 23,000 BTU	34 7/8"	70 1/2"	16 7/8"	19 7/8" x 7 7/8"	19 7/8" x 11 7/8"
30,000 - 36,000 BTU	39 7/8"	70 1/2"	16 7/8"	27 7/8" x 7 7/8"	27 7/8" x 13 7/8"
43,000 - 57,500 BTU	43 7/8"	84 7/8"	22 1/2"	29 7/8" x 9 7/8"	29 7/8" x 15 7/8"
67,000 - 69,500 BTU	43 7/8"	94 7/8"	22 1/4"	29 7/8" x 9 7/8"	29 7/8" x 15 7/8"

*MATTICKS INDUSTRIES, INC. / 11232 BRITTMOORE PARK DR.
HOUSTON, TX 77041 / P: 832-243-0662 F: 832-243-0660
www.matticks.com*